

PRODUCT IDENTIFICATION



JPK **0608** – **100 K**

Tolerance *K±10%, M±20%

Inductance

Size

S: Salient , A: Axial


RH: Shielding

Type

TYPE


All series could be customized to design for customers. For detail, please contact JANTEK.

JPK




Part	A	B	C
JPK 0406	5.5 Max.	7.5 Max.	16.0 ± 3.0
JPK 0507	6.5 Max.	8.5 Max.	16.0 ± 3.0
JPK 0608	7.5 Max.	9.5 Max.	16.0 ± 3.0
JPK 0807	9.5 Max.	8.5 Max.	16.0 ± 3.0
JPK 0810	9.5 Max.	11.5 Max.	16.0 ± 3.0
JPK 0912	10.5 Max.	13.5 Max.	16.0 ± 3.0
JPK 1010	11.5 Max.	11.5 Max.	16.0 ± 3.0
JPK 1012	11.5 Max.	13.5 Max.	16.0 ± 3.0
JPK 1016	11.5 Max.	17.5 Max.	16.0 ± 3.0
JPK 1216	13.5 Max.	17.5 Max.	16.0 ± 3.0
JPK 1415	15.5 Max.	16.5 Max.	16.0 ± 3.0
JPK 1618	17.5 Max.	19.5 Max.	16.0 ± 3.0

JPKS




For detail, please contact JANTEK.

JPKA



For detail, please contact JANTEK.

JPKRH



For detail, please contact JANTEK.

