SPECIFICATION FOR APPROVAL

COMMODITY	COMMON MODE FILTER CHOKE	SPEC NO.	SP-0200305003
ITEM	JACM 4532-220 Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)



	DIM.	TOL.
A	4.50	±0.20
B	3.20	±0.20
C	2.80	±0.20
D1	0.75	±0.20
D2	0.85	±0.20
D3	0.60	±0.20

(2) ELECTRICAL CHARACTERISTIC

Common mode Impedance	500 (min) 1200 (typ)		Ω
Test Frequency	10		MHz
Common mode Inductance	22	+50% -30%	μH
Test Frequency	100		KHz
DC Resistance	1.0	(max)	Ω
Rated Current	310	(max)	mA
Rated Volt.	50	(max)	Vdc
IR	10	(min)	MΩ

TEST INSTRUMENTS.

- ☑ AGILENT 4294A Precision Impedance Analyzer.
- ☐ AGILENT 4285A Precision L.C.R. Meter.
- ☐ HP-4286A RF L.C.R. Meter.
- ☑ ZENTECH 3302 Automatic Components Analyzer.
- ☐ ZENTECH 101 L.C.R. Meter.
- ☐ WAYNE KERR 6420 Precision Impedance Analyzer.
- ☑ ZENTECH 1320 BIAS CURRENT.
- ☑ ZENTECH 502AC Resistance Merter.
- ☐ ADEX AX-1155B DC Low Ohm Meter.

REMARK：

. Operating temperature-40~+150℃(Including self - temperature rise)

PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN
	楊偉鐘	美秀琴	陳秀月

JANTEK
TEL：886-2-2689-4971 FAX：886-2-2689-4260
E-mail：jantek@jantek-elec.com.tw
Web-Site：www.jantek-elec.com.tw

TEST REPORT

SPEC NO： SP-0200305003

Typical Impedance v.s. Frequency Curve



Check by：	Test by：
姜秀琴	陳秀月

JANTEK

TEL：886-2-2689-4971 FAX：886-2-2689-4260
E-mail：jantek@jantek-elec.com.tw
Web-Site：www.jantek-elec.com.tw