


SPECIFICATION FOR APPROVAL

COMMODITY	FERRITE BEADS	SPEC NO.	SP-060908020
ITEM	RH 3.5×9.0×0.8 Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)			DIM.	TOL.
		A	3.5	± 0.15
		B	9.0	± 0.30
		C	52.0	± 2.00
		D	0.68	Max
		E	6.0	± 1.00
		F	5.0	± 0.50

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
IMPEDANCE at Z 1	60 (min) Ω	☒ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter. ☐ CHROMA 3302 Automatic Components Analyzer. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☐ ZENTECH 1320 BIAS CURRENT. ☐ BK PRECISION 2840 DC Resistance Meter ☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter ☐ WAYNE KERR HI-POT TESTER 7600
IMPEDANCE at Z 2	100 (min) Ω	
TEST FREQUENCY at Z 1	25 MHz	
TEST FREQUENCY at Z 2	100 MHz	


REMARK :

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-060908020

Typical Impedance v.s. Frequency Curve



Test Instrument :

HP-4286A RF L.C.R. Meter.

Testing Condition :

Temperature : 25 to 28°C

Humidity : 60 to 70 % RH

Check by :



Test by :

