# SPECIFICATION FOR APPROVAL

| COMMODITY | WIDE BAND CHOKE | SPEC NO. | SP-060927081 |
|---|---|---|---|
| ITEM | K5B R6H 2.0Ts Green | 版本：A | 表單編號：QR-012-02 |

(1) DIMENSION: (UNIT: mm)




| | DIM. | TOL. |
|---|---|---|
| A | 6.00 | ± 0.25 |
| B | 10.00 | ± 0.3 |
| C | 25.00 | ± 2.0 |
| D | 0.50 | ± 0.1 |
| E | 1.50 | Max |
| | | |
| | | |
| | | |
| | | |
| | | |

(2) ELECTRICAL CHARACTERISTIC

| | | | |
|---|---|---|---|
| IMPEDANCE at Z1 | 200 | (min) | Ω |
| IMPEDANCE at Z2 | 450 | (min) | Ω |
| IMPEDANCE at Z3 | 480 | (min) | Ω |
| TEST FREQUENCY at Z1 | 10 | | MHz |
| TEST FREQUENCY at Z2 | 50 | | MHz |
| TEST FREQUENCY at Z3 | 100 | | MHz |
| | | | |

TEST INSTRUMENTS.

- [x] AGILENT 4294A Precision Impedance Analyzer
- [ ] Agilent 4287A RF LCR Meter
- [ ] AGILENT 4285A Precision L.C.R.
- [ ] HP-4286A RF L.C.R. Meter.
- [ ] CHROMA 3302 Automatic Components Analyzer.
- [ ] WAYNE KERR 6420 Precision Impedance Analyzer.
- [ ] ZENTECH 1320 BIAS CURRENT.
- [ ] BK PRECISION 2840 DC Resistance Meter
- [ ] ZENTECH 502AC Resistance Merter
- [ ] ADEX AX-1155B DC Low Ohm Meter
- [ ] WAYNE KERR HI-POT TESTER 7600

REMARK：

PURCHASER CONFIRMED：

| APPROVED | CHECKED | DRAWN |
|---|---|---|
| 楊 偉鏗 | 姜 秀琴 | 陳 秀月 |


JANTEK

TEL：886-2-2689-4971 FAX：886-2-2689-4260
E-mail：jantek@jantek-elec.com.tw
Web-Site：www.jantek-elec.com.tw

# TEST REPORT

SPEC NO： SP-060927081

Typical Impedance v.s. Frequency Curve




Test Instrument：

HP-4286A RF L.C.R. Meter.

Testing Condition：

Temperature： 25 to 28℃

Humidity： 60 to 70 % RH

| Check by： | Test by： |
|---|---|
| 姜 秀琴 | 陳 秀月 |


JANTEK

TEL：886-2-2689-4971 FAX：886-2-2689-4260

E-mail：jantek@jantek-elec.com.tw

Web-Site：www.jantek-elec.com.tw