


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0100205020
ITEM	JQH 322520-271K Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
 Marking LAND PATTERNS(mm)	A	3.2	±0.3
	B	2.5	±0.2
	C	2.0	±0.3
	D	0.7	Min.
	E	0.7	Min.
	F	1.0	REF.
	G	2.0	REF.
	H	1.5	REF.

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	270 ± 10% μ H	☒ AGILENT 4294A Precision Impedance Analyzer. ☐ AGILENT 4285A Precision L.C.R. Meter. ☐ HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	1 MHz	☒ ZENTECH 3302 Automatic Components Analyzer. ☐ ZENTECH 101 L.C.R. Meter.
Q	40 (min)	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
TEST FREQUENCY	796 KHz	☒ ZENTECH 1320 BIAS CURRENT. ☒ ZENTECH 502AC Resistance Merter.
SRF	5.0 (min) MHz	☒ ADEX AX-1155B DC Low Ohm Meter.
RDC	12.5 (max) Ω	
IDC	65 (max) mA	

REMARK :

- . Operating temp. : -30℃ to 105℃ . (Including coils self-temperature rise)
- . Storage Temperature Component: -30℃ to 105℃ .
- . Rated Current: It is either the inductance is 10% lower than its initial value in DC.
- . Saturation characteristics or temperature raise becomes $\Delta T=20^{\circ}\text{C}$ ($T_a=25^{\circ}\text{C}$), whichever is lower.

PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN
			