


SPECIFICATION FOR APPROVAL

COMMODITY	DATALINE NOISE FILTER		SPEC NO.	SP-060922033
ITEM	JMLF 0820	Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	19.50	± 1.0
	B	23.00	± 1.0
	C	8.10	± 0.5
	D	20.00	± 1.0
	E	26.00	± 1.0

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
IMPEDANCE at Z 1	40 (min)	Ω	☒ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter. ☐ CHROMA 3302 Automatic Components Analyzer. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☐ ZENTECH 1320 BIAS CURRENT. ☐ BK PRECISION 2840 DC Resistance Meter ☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter ☐ WAYNE KERR HI-POT TESTER 7600
IMPEDANCE at Z 2	100 (min)	Ω	
TEST FREQUENCY at Z 1	25	MHz	
TEST FREQUENCY at Z 2	100	MHz	

REMARK :


Winding : Φ 0.65×100 mm 2UEW 1Ts

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-060922033

Typical Impedance v.s. Frequency Curve



Test Instrument :

HP-4286A RF L.C.R. Meter.

Testing Condition :

Temperature : 25 to 28°C

Humidity : 60 to 70 % RH

Check by :



Test by :

