


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0190104023
ITEM	JNR 8040H-151M	Green	版本：A 表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	8.00	±0.3
	B	8.00	±0.3
	C	3.70	±0.3
	D	2.40	±0.3
	E	6.30	±0.3

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	150 ± 20% μ H	☐ AGILENT 4294A Precision Impedance Analyzer.
TEST FREQUENCY	1 MHz	☐ AGILENT 4285A Precision L.C.R.
TEST VOLT	1 V	☐ HP-4286A RF L.C.R. Meter.
RDC	410 ± 20% m Ω	☒ ZENTECH 3302 Automatic Components Analyzer.
Isat	1.20 (typ) A 1.03 (max)	☐ ZENTECH 101 L.C.R. Meter.
Irms	0.98 (typ) A 0.90 (max)	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
		☒ ZENTECH 1320 BIAS CURRENT.
		☒ ZENTECH 502AC Resistance Merter.
		☐ ADEX AX-1155B DC Low Ohm Meter.

REMARK :


1. All test data referenced to 25°C ambient
2. Isat : Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Irms : Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C

PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0190104023

Typical Performance Curves



Test Instrument :

ZENTECH 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :



Test by :



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw

