


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0131204009
ITEM	JNR 252010U-150M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	2.50	-0.1/+0.2
	B	2.00	-0.1/+0.2
	C	1.00	Max.
	D	0.85	Ref.
	E	0.80	Ref.

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	15 ± 20% μH	☒ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter
TEST FREQUENCY	1 MHz	☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
TEST VOLT	0.1 V	☒ CHROMA 3302 Automatic Components Analyzer.
RDC	0.750 ± 20% Ω	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
Isat	0.55 (typ.) 0.45 (max) A	☒ ZENTECH 1320 BIAS CURRENT. ☒ BK PRECISION 2840 DC Resistance Meter
Irms	0.55 (typ.) 0.50 (max) A	☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter
		☐ WAYNE KERR HI-POT TESTER 7600

REMARK：


1. Isat：Saturation Current (Isat) will cause L0 to drop approximately 30%
2. Irms：Heat Rated Current (Irms) will cause the coil temperature rise approximately Δt40℃
3. Rated DC current: The lower value of Irms and Isat.

PURCHASER CONFIRMED：	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0131204009

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer.

ZENTECH 1320 BIAS CURRENT.

Testing Condition :

Temperature : 25 to 28°C

Humidity : 60 to 70 % RH

Check by :



Test by :

