

# SPECIFICATION FOR APPROVAL

|           |                                                                                   |          |                |
|-----------|-----------------------------------------------------------------------------------|----------|----------------|
| COMMODITY | SMD POWER COIL                                                                    | SPEC NO. | SP-0160608001  |
| ITEM      | JTP 0302-391K <span style="border: 1px solid black; padding: 0 2px;">Green</span> | 版本：A     | 表單編號：QR-012-02 |

| (1) DIMENSION: (UNIT: mm) |   | DIM. | TOL. |
|---------------------------|---|------|------|
|                           | A | 3.5  | ±0.3 |
|                           | B | 3.0  | ±0.3 |
|                           | C | 2.3  | ±0.3 |
|                           | D | 3.5  | ±0.3 |
|                           | E | 1.4  | REF. |
|                           | F | 0.8  | REF. |
|                           | G | 3.0  | REF. |
|                           |   |      |      |
|                           |   |      |      |
|                           |   |      |      |

| (2) ELECTRICAL CHARACTERISTIC |             |     | TEST INSTRUMENTS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------------------|-------------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| INDUCTANCE                    | 390 ± 10%   | μ H | <input checked="" type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer<br><input checked="" type="checkbox"/> Agilent 4287A RF LCR Meter<br><input type="checkbox"/> AGILENT 4285A Precision L.C.R.<br><input type="checkbox"/> HP-4286A RF L.C.R. Meter.<br><input checked="" type="checkbox"/> CHROMA 3302 Automatic Components Analyzer.<br><input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.<br><input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT.<br><input checked="" type="checkbox"/> BK PRECISION 2840 DC Resistance Meter<br><input type="checkbox"/> ZENTECH 502AC Resistance Merter<br><input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter<br><input type="checkbox"/> WAYNE KERR HI-POT TESTER 7600 |
| TEST FREQUENCY                | 100         | KHz |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| TEST VOLT                     | 0.25        | V   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| RDC                           | 14.56 (max) | Ω   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| IDC                           | 0.09 (max)  | A   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                               |             |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                               |             |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## REMARK :

. This indicates the value of current when the inductance is 10% lower than its initial value at D.C. superimposition or D.C. current when at t=40°C, whichever is lower. (Ta=20°C)

| PURCHASER CONFIRMED : | APPROVED | CHECKED | DRAWN |
|-----------------------|----------|---------|-------|
|                       |          |         |       |