


SPECIFICATION FOR APPROVAL

COMMODITY	SMD AIR WOUND COIL	SPEC NO.	SP-061002060
ITEM	JAS 292A-03J Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	1.42	±0.13
	B	0.89	±0.25
	C	1.37	±0.15
	D	2.21	±0.25
	E	1.83	±0.25

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	2.55 ± 5%	nH	☐ AGILENT 4294A Precision Impedance Analyzer ☒ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter. ☒ CHROMA 3302 Automatic Components Analyzer. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☒ ZENTECH 1320 BIAS CURRENT. ☒ BK PRECISION 2840 DC Resistance Meter ☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter ☐ WAYNE KERR HI-POT TESTER 7600
Q	100	(min)	
TEST FREQUENCY	800	MHz	
TEST VOLT	0.25	V	
SRF	8.2	(min) GHz	
RDC	5.0	(max) mΩ	
IDC	1.6	(max) A	

REMARK :

- Operating temp. : -40°C to +125°C
- For temperature rise : 15°C

PURCHASER CONFIRMED :

APPROVED	CHECKED	DRAWN
		