

SPECIFICATION FOR APPROVAL

COMMODITY	HIGH FREQUENCY WOUND CHIP INDUCTOR	SPEC NO.	SP-060926038
ITEM	JWI 0402C-20NJ Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	1.00	±0.1
	B	0.55	±0.1
	C	0.50	±0.1
	D	0.50	(REF)
	E	0.20	±0.1

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	20 ± 5%	nH	☐ AGILENT 4294A Precision Impedance Analyzer ☒ Agilent 4287A RF LCR Meter
TEST FREQUENCY	250	MHz	☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
Q	25 (min)		☒ CHROMA 3302 Automatic Components Analyzer.
TEST FREQUENCY	250	MHz	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
SRF	3000 (min)	MHz	☒ ZENTECH 1320 BIAS CURRENT.
RDC	0.25 (max)	Ω	☒ BK PRECISION 2840 DC Resistance Meter
IDC	420 (max)	mA	☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter ☐ WAYNE KERR HI-POT TESTER 7600

REMARK :

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN