

SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-060802090
ITEM	JSPK 0804-151M	Green	版本：A 表單編號：QRRD-01-02

(1) DIMENSION: (UNIT: mm)

	DIM.	TOL.
A	9.0	Max.
B	5.5	Max.
C	9.5	Max.
D	13.5	Max.
E	2.92	REF.
F	7.37	REF.
G	2.79	REF.

LAND PATTERNS(mm)

含浸凡立水

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	150 ± 20% μ H	☒ AGILENT 4294A Precision Impedance Analyzer.
TEST FREQUENCY	100 KHz	☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
TEST VOLT	0.1 V	☒ ZENTECH 3302 Automatic Components Analyzer.
RDC	0.40 (max) Ω	☐ ZENTECH 101 L.C.R. Meter. ☐ WAYNE KERR 6420 Precision Impedance Analyzer.
Isat	1.0 (max) A	☒ ZENTECH 1320 BIAS CURRENT.
Irms	1.0 (max) A	☒ ZENTECH 502AC Resistance Merter. ☐ ADEX AX-1155B DC Low Ohm Meter.

REMARK :

1. Inductance drop = 10% typ. at IDC.
2. $\Delta T = 40^{\circ}\text{C}$ typ. at IDC.

PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN
			