

SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0230418005
ITEM	JPRD 0502-4R1M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
		A	5.7 ±0.3
		B	5.7 ±0.3
		C	2.0 Max.
		D	8.2 Max.

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	4.1 ± 20%	μ H	☒ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	10	KHz	☒ CHROMA 3302 Automatic Components Analyzer. ☐ WAYNE KERR 6420 Precision Impedance Analyzer.
TEST VOLT	0.25	V	☒ ZENTECH 1320 BIAS CURRENT. ☒ BK PRECISION 2840 DC Resistance Meter
RDC	0.063 (max)	Ω	☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter
IDC	1.95 (max)	A	☐ WAYNE KERR HI-POT TESTER 7600

REMARK :

- Inductance drop = 35% typ at IDC
- ΔT = 40°C rise typ at IDC

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN