


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-060802028
ITEM	JSB 1003-680M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	10.5	Max.
	B	10.5	Max.
	C	3.5	Max.
	D	2.5	REF.
	E	5.6	REF.
	F	3.2	REF.

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	68 ± 20% μH	☒ AGILENT 4294A Precision Impedance Analyzer
TEST FREQUENCY	1 KHz	☐ Agilent 4287A RF LCR Meter
TEST VOLT	0.25 V	☐ AGILENT 4285A Precision L.C.R.
RDC	0.324 (max) Ω	☐ HP-4286A RF L.C.R. Meter.
IDC	0.90 (max) A	☒ CHROMA 3302 Automatic Components Analyzer.
		☐ WAYNE KERR 6420 Precision Impedance Analyzer.
		☒ ZENTECH 1320 BIAS CURRENT.
		☒ BK PRECISION 2840 DC Resistance Meter
		☐ ZENTECH 502AC Resistance Merter
		☐ ADEX AX-1155B DC Low Ohm Meter
		☐ WAYNE KERR HI-POT TESTER 7600

REMARK :

1. Inductance drop = 25% typ at IDC
2. ΔT = 40°C rise typ at IDC

PURCHASER CONFIRMED :

APPROVED	CHECKED	DRAWN
		