


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-091209002
ITEM	JPRH 0704-3R3M-2R8-A Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	7.3	±0.2
	B	7.3	±0.2
	C	4.5	Max.
	D	1.6	REF.
	E	4.8	REF.
	F	2.2	REF.

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	3.3 ± 20%	μ H	☐ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter. ☒ CHROMA 3302 Automatic Components Analyzer. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☒ ZENTECH 1320 BIAS CURRENT. ☒ BK PRECISION 2840 DC Resistance Meter ☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter ☐ WAYNE KERR HI-POT TESTER 7600
TEST FREQUENCY	100	KHz	
TEST VOLT	0.1	V	
RDC	46.2 (max)	mΩ	
Isat	4.0 (max)	A	
Irms	2.8 (max)	A	

REMARK :

1. Inductance drop = 25% typ at Isat
2. ΔT = 40°C rise typ at Irms

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			