


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0230330012
ITEM	JRPI 0402P-R10M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.	
	A	4.45	± 0.25	
	B	4.10	± 0.20	
	C	1.80	± 0.20	
	D	0.80	± 0.25	
	E	2.00	± 0.20	

(2) ELECTRICAL CHARACTERISTIC	TEST INSTRUMENTS.	
INDUCTANCE	0.10 ± 20% μH	<input type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer
TEST FREQUENCY	100 KHz	<input type="checkbox"/> Agilent 4287A RF LCR Meter
TEST VOLT	1 V	<input type="checkbox"/> AGILENT 4285A Precision L.C.R.
RDC	2.9 (typ.) 3.2 (max) mΩ	<input type="checkbox"/> HP-4286A RF L.C.R. Meter.
Isat	26.0 (typ.) 22.0 (max) A	<input checked="" type="checkbox"/> CHROMA 3302 Automatic Components Analyzer.
Irms	16.0 (typ.) 14.0 (max) A	<input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.
		<input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT.
		<input checked="" type="checkbox"/> BK PRECISION 2840 DC Resistance Meter
		<input type="checkbox"/> ZENTECH 502AC Resistance Merter
		<input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter
		<input type="checkbox"/> WAYNE KERR HI-POT TESTER 7600

REMARK :


1. All test data referenced to 25°C ambient.
2. Saturation Current (Isat) will cause L0 to drop approximately 30%
3. Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0230330012

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw