


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0230406027
ITEM	JRPI 0624P-3R3M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	7.10	± 0.30
	B	6.70	± 0.20
	C	2.20	± 0.20
	D	1.60	± 0.30
	E	3.00	± 0.20

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	3.3 ± 20%	μ H	☐ AGILENT 4294A Precision Impedance Analyzer
TEST FREQUENCY	100	KHz	☐ Agilent 4287A RF LCR Meter
TEST VOLT	1	V	☐ AGILENT 4285A Precision L.C.R.
RDC	31.0 (typ.) 38.0 (max)	mΩ	☐ HP-4286A RF L.C.R. Meter.
Isat	8.5 (typ.) 7.0 (max)	A	☒ CHROMA 3302 Automatic Components Analyzer.
Irms	8.0 (typ.) 6.0 (max)	A	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
			☒ ZENTECH 1320 BIAS CURRENT.
			☒ BK PRECISION 2840 DC Resistance Meter
			☐ ZENTECH 502AC Resistance Merter
			☐ ADEX AX-1155B DC Low Ohm Meter
			☐ WAYNE KERR HI-POT TESTER 7600

REMARK :


1. All test data referenced to 25°C ambient.
2. Saturation Current (Isat) will cause L0 to drop approximately 30%
3. Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0230406027

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :



Test by :



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw