


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0221121002
ITEM	JNR 252012P-1R5M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	2.50	-0.1/+0.2
	B	2.00	-0.1/+0.2
	C	1.20	Max
	D	0.75	Ref
	E	1.00	Ref

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	1.5 ± 20% μ H	☐ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	1 MHz	☒ CHROMA 3302 Automatic Components Analyzer.
TEST VOLT	1 V	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
RDC	0.050 (typ.) Ω 0.060 (max)	☒ ZENTECH 1320 BIAS CURRENT.
Isat	3.80 (typ.) A 3.20 (max)	☒ BK PRECISION 2840 DC Resistance Meter
Irms	3.50 (1) (typ.) A 4.00 (2)	☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter
Irms	3.00 (1) (max) A 3.50 (2)	☐ WAYNE KERR HI-POT TESTER 7600

REMARK :

1. All test data referenced to 25°C ambient
2. Isat : Based on inductance change ($\Delta L/L_0$: $\leq 30\%$)
3. Irms : Based on temperature rise (ΔT : 40°C.) Max


PURCHASER CONFIRMED :

APPROVED	CHECKED	DRAWN
		

TEST REPORT

SPEC NO : SP-0221121002

Typical Performance Curves



Test Instrument :

ZENTECH 3302 Automatic Components Analyzer

ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C

Humidity : 60 to 70 % RH

Check by :



Test by :

