


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0190503013
ITEM	JRPI 1206M-1R2M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	13.5	± 0.5
	B	12.5	± 0.3
	C	5.7	± 0.3
	D	2.3	± 0.3
	E	4.7	± 0.3

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	1.2 ± 20% μ H	☐ AGILENT 4294A Precision Impedance Analyzer. ☐ AGILENT 4285A Precision L.C.R. Meter. ☐ HP-4286A RF L.C.R. Meter. ☒ ZENTECH 3302 Automatic Components Analyzer. ☐ ZENTECH 101 L.C.R. Meter. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☒ ZENTECH 1320 BIAS CURRENT. ☒ ZENTECH 502AC Resistance Merter. ☐ ADEX AX-1155B DC Low Ohm Meter.
TEST FREQUENCY	100 KHz	
TEST VOLT	1 V	
RDC	2.1 (typ.) 2.8 (max) m Ω	
Isat 1	44 (typ.) A	
Isat 2	51 (typ.) A	
Irms	28 (typ.) A	

REMARK :

- All test data referenced to 25°C ambient
- Saturation Current (Isat 1) will cause L0 to drop approximately 20%
Saturation Current (Isat 2) will cause L0 to drop approximately 30%
- Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C


PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0190503013

Typical Performance Curves

JRPI 1206M-1R2



Test Instrument :

ZENTECH 3302 Automatic Components Analyzer

ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C

Humidity : 60 to 70 % RH

Check by :



Test by :



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260

E-mail : jantek@jantek-elec.com.tw

Web-Site : www.jantek-elec.com.tw