

# SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0220701029
ITEM	JRPI 0603FV-R33M <span style="border: 1px solid black; padding: 2px;">Green</span>	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.	
	A	7.20	±0.20	
	B	6.90	±0.20	
	C	2.80	±0.20	
	D	5.55	±0.30	
	E	1.40	±0.20	
	F	2.60	±0.25	

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	0.33 ± 20%	μ H	<input checked="" type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer <input type="checkbox"/> Agilent 4287A RF LCR Meter
TEST FREQUENCY	100	KHz	<input type="checkbox"/> AGILENT 4285A Precision L.C.R. <input type="checkbox"/> HP-4286A RF L.C.R. Meter.
TEST VOLT	0.1	V	<input checked="" type="checkbox"/> CHROMA 3302 Automatic Components Analyzer.
RDC	2.25 (typ.) 2.50 (max)	mΩ	<input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.
Isat	32.0 (typ.) 28.0 (max)	A	<input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT. <input checked="" type="checkbox"/> BK PRECISION 2840 DC Resistance Meter
Irms 20°C rise	20.0 (typ.)	A	<input type="checkbox"/> ZENTECH 502AC Resistance Merter <input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter
Irms 40°C rise	25.0 (typ.)	A	<input type="checkbox"/> WAYNE KERR HI-POT TESTER 7600

**REMARK :**

1. All test data referenced to 25°C ambient
2. Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Rated operating voltage(across inductor) 40V Ref.
4. Rated DC current: The lower value of Irms and Isat.


<b>PURCHASER CONFIRMED :</b>	<b>APPROVED</b>	<b>CHECKED</b>	<b>DRAWN</b>



# TEST REPORT

SPEC NO : SP-0220701029

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer  
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C  
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260  
E-mail : jantek@jantek-elec.com.tw  
Web-Site : www.jantek-elec.com.tw