


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0220518035
ITEM	JRPI 1508F-4R7M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
		A	17.50 ±0.30
		B	16.50 ±0.30
		C	7.70 ±0.30
		D	13.20 ±0.50
		E	3.20 ±0.20
		F	7.00 ±0.30

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	4.7 ± 20% μ H	☒ AGILENT 4294A Precision Impedance Analyzer.
TEST FREQUENCY	100 KHz	☐ AGILENT 4285A Precision L.C.R. Meter.
TEST VOLT	0.1 V	☐ HP-4286A RF L.C.R. Meter.
RDC	4.30 (typ.) 5.16 (max) m Ω	☒ ZENTECH 3302 Automatic Components Analyzer.
Isat	37.0 (typ.) 32.0 (max) A	☐ ZENTECH 101 L.C.R. Meter.
Irms 20°C rise	20.0 (typ.) A	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
Irms 40°C rise	26.5 (typ.) A	☒ ZENTECH 1320 BIAS CURRENT.
		☒ ZENTECH 502AC Resistance Merter.
		☐ ADEX AX-1155B DC Low Ohm Meter.

REMARK :


1. All test data referenced to 25°C ambient
2. Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Rated operating voltage(across inductor) 40V ref.
4. Rated DC Current : The less value whith is Irms or Isat

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0220518035

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :



Test by :



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw