


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0220701043
ITEM	JRPI 0605FV-1R8M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	7.20	±0.20
	B	6.90	±0.20
	C	4.80	±0.20
	D	5.30	±0.30
	E	1.40	±0.20
	F	2.60	±0.25

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	1.8 ± 20%	μ H	☒ AGILENT 4294A Precision Impedance Analyzer
TEST FREQUENCY	100	KHz	☐ Agilent 4287A RF LCR Meter
TEST VOLT	0.1	V	☐ AGILENT 4285A Precision L.C.R.
RDC	6.40 (typ.) 7.10 (max)	mΩ	☐ HP-4286A RF L.C.R. Meter.
Isat	18.5 (typ.) 13.5 (max)	A	☒ CHROMA 3302 Automatic Components Analyzer.
Irms 20°C rise	12.0 (typ.)	A	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
Irms 40°C rise	16.0 (typ.)	A	☒ ZENTECH 1320 BIAS CURRENT.
			☒ BK PRECISION 2840 DC Resistance Meter
			☐ ZENTECH 502AC Resistance Merter
			☐ ADEX AX-1155B DC Low Ohm Meter
			☐ WAYNE KERR HI-POT TESTER 7600

REMARK :


1. All test data referenced to 25°C ambient
2. Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Rated operating voltage(across inductor) 40V Ref.
4. Rated DC current: The lower value of Irms and Isat.

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0220701043

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw