


# SPECIFICATION FOR APPROVAL

|           |                                                                                     |          |                |
|-----------|-------------------------------------------------------------------------------------|----------|----------------|
| COMMODITY | SMD POWER COIL                                                                      | SPEC NO. | SP-0181113035  |
| ITEM      | JRPI 0318V-4R7M <span style="border: 1px solid black; padding: 0 2px;">Green</span> | 版本：A     | 表單編號：QR-012-02 |

| (1) DIMENSION: (UNIT: mm)                                                         |  | DIM. | TOL.           |
|-----------------------------------------------------------------------------------|--|------|----------------|
|  |  | A    | 3.50<br>± 0.30 |
|                                                                                   |  | B    | 3.20<br>± 0.20 |
|                                                                                   |  | C    | 1.60<br>± 0.20 |
|                                                                                   |  | D    | 0.70<br>± 0.20 |
|                                                                                   |  | E    | 1.20<br>± 0.20 |
|                                                                                   |  |      |                |
|                                                                                   |  |      |                |
|                                                                                   |  |      |                |
|                                                                                   |  |      |                |
|                                                                                   |  |      |                |

| (2) ELECTRICAL CHARACTERISTIC |                                | TEST INSTRUMENTS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| INDUCTANCE                    | 4.7 ± 20% $\mu$ H              | <input type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer.<br><input type="checkbox"/> AGILENT 4285A Precision L.C.R. Meter.<br><input type="checkbox"/> HP-4286A RF L.C.R. Meter.<br><input checked="" type="checkbox"/> ZENTECH 3302 Automatic Components Analyzer.<br><input type="checkbox"/> ZENTECH 101 L.C.R. Meter.<br><input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.<br><input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT.<br><input checked="" type="checkbox"/> ZENTECH 502AC Resistance Merter.<br><input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter. |
| TEST FREQUENCY                | 100 KHz                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| TEST VOLT                     | 1 V                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| RDC                           | 180.0 (typ.)<br>208.0 (max) mΩ |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Isat                          | 2.9 (typ.) A                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Irms                          | 2.3 (typ.) A                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                               |                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## REMARK :


1. All test data referenced to 25°C ambient
2. Saturation Current (Isat) will cause L0 to drop approximately 30%
3. Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C
4. Compatible with AEC-Q200

| PURCHASER CONFIRMED | APPROVED                                                                             | CHECKED                                                                               | DRAWN                                                                                 |
|---------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                     |  |  |  |

# TEST REPORT

SPEC NO : SP-0181113035

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer  
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28 $^{\circ}C$   
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260  
E-mail : jantek@jantek-elec.com.tw  
Web-Site : www.jantek-elec.com.tw