

SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0220704013
ITEM	JRPI 0703FV-5R6M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.	
	A	8.40	±0.30	
	B	8.00	±0.30	
	C	2.90	±0.20	
	D	6.20	±0.30	
	E	1.75	±0.20	
	F	3.15	±0.25	

(2) ELECTRICAL CHARACTERISTIC	TEST INSTRUMENTS.	
INDUCTANCE	5.6 ± 20% μH	<input checked="" type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer <input type="checkbox"/> Agilent 4287A RF LCR Meter <input type="checkbox"/> AGILENT 4285A Precision L.C.R. <input type="checkbox"/> HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	100 KHz	<input checked="" type="checkbox"/> CHROMA 3302 Automatic Components Analyzer. <input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.
TEST VOLT	0.1 V	<input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT. <input checked="" type="checkbox"/> BK PRECISION 2840 DC Resistance Meter
RDC	30.1 (typ.) 33.2 (max) mΩ	<input type="checkbox"/> ZENTECH 502AC Resistance Merter <input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter
Isat	12.5 (typ.) 11.5 (max) A	<input type="checkbox"/> WAYNE KERR HI-POT TESTER 7600
Irms 20°C rise	5.3 (typ.) A	
Irms 40°C rise	7.3 (typ.) A	

REMARK :

1. All test data referenced to 25°C ambient
2. Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Rated operating voltage(across inductor) 40V Ref.
4. Rated DC current: The lower value of Irms and Isat.


PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN



TEST REPORT

SPEC NO : SP-0220704013

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw