

SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0220704036
ITEM	JRPI 1006FV-5R6M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	11.90	±0.30
	B	11.00	±0.30
	C	5.70	±0.30
	D	8.80	±0.30
	E	2.40	±0.20
	F	4.50	±0.30

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	5.6 ± 20%	μ H	<input checked="" type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer <input type="checkbox"/> Agilent 4287A RF LCR Meter
TEST FREQUENCY	100	KHz	<input type="checkbox"/> AGILENT 4285A Precision L.C.R. <input type="checkbox"/> HP-4286A RF L.C.R. Meter.
TEST VOLT	0.1	V	<input checked="" type="checkbox"/> CHROMA 3302 Automatic Components Analyzer.
RDC	10.80 (typ.) 11.90 (max)	mΩ	<input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.
Isat	20.0 (typ.) 17.0 (max)	A	<input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT. <input checked="" type="checkbox"/> BK PRECISION 2840 DC Resistance Meter
Irms 20°C rise	7.0 (typ.)	A	<input type="checkbox"/> ZENTECH 502AC Resistance Merter <input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter
Irms 40°C rise	12.0 (typ.)	A	<input type="checkbox"/> WAYNE KERR HI-POT TESTER 7600

REMARK :

1. All test data referenced to 25°C ambient
2. Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Rated operating voltage(across inductor) 40V Ref.
4. Rated DC current: The lower value of Irms and Isat.

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260


E-mail : jantek@jantek-elec.com.tw

Web-Site : www.jantek-elec.com.tw

TEST REPORT

SPEC NO : SP-0220704036

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw