


SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-0220803006
ITEM	JRPI 0403FLV-3R3M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	4.40	±0.20
	B	4.40	±0.20
	C	2.80	±0.20
	D	3.40	±0.30
	E	0.88	±0.20
	F	1.60	±0.25

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS
INDUCTANCE	3.3 ± 20%	μ H	☒ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	100	KHz	
TEST VOLT	0.1	V	
RDC	26.0 (typ.) 28.6 (max)	mΩ	☐ CHROMA 3302 Automatic Components Analyzer. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☒ ZENTECH 1320 BIAS CURRENT.
Isat	1 3.3 (typ.)	A	
	2 4.8 (typ.)	A	
	3 6.2 (typ.)	A	
	3 5.3 (max)	A	☒ BK PRECISION 2840 DC Resistance Meter ☐ ZENTECH 502AC Resistance Merter
Irms 20°C rise	5.0 (typ.)	A	
Irms 40°C rise	6.6 (typ.)	A	☐ WAYNE KERR HI-POT TESTER 7600

REMARK :


- All test data referenced to 25°C ambient.
- Current that causes the specified temperature rise from 25°C ambient.
- Saturation Current (Isat 1) will cause L0 to drop approximately 10%.
 Saturation Current (Isat 2) will cause L0 to drop approximately 20%.
 Saturation Current (Isat 3) will cause L0 to drop approximately 30%.

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0220803006

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C
Humidity : 60 to 70 % RH

Check by :

姜秀琴

Test by :

陳秀月



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw