



LAND PATTERNS(mm)

DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 0703	7.3 ± 0.2	7.3 ± 0.2	3.2 ± 0.2	1.50	4.80	2.20

SERIES LIST

No.	Part No.	L (μ H)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRH 0703-2R2M - ☐	2.2	1	0.032	3.20
2	JPRH 0703-4R7M - ☐	4.7	1	0.042	2.90
3	JPRH 0703-8R2M - ☐	8.2	1	0.092	1.70
4	JPRH 0703-100M - ☐	10	1	0.072	1.68
5	JPRH 0703-120M - ☐	12	1	0.098	1.52
6	JPRH 0703-150M - ☐	15	1	0.130	1.33
7	JPRH 0703-180M - ☐	18	1	0.140	1.20
8	JPRH 0703-220M - ☐	22	1	0.190	1.07
9	JPRH 0703-270M - ☐	27	1	0.210	0.96
10	JPRH 0703-330M - ☐	33	1	0.240	0.91
11	JPRH 0703-390M - ☐	39	1	0.320	0.77
12	JPRH 0703-470M - ☐	47	1	0.360	0.76
13	JPRH 0703-560M - ☐	56	1	0.470	0.68
14	JPRH 0703-680M - ☐	68	1	0.520	0.61
15	JPRH 0703-820M - ☐	82	1	0.690	0.57
16	JPRH 0703-101M - ☐	100	1	0.790	0.50
17	JPRH 0703-121M - ☐	120	1	0.890	0.45
18	JPRH 0703-151M - ☐	150	1	1.270	0.43
19	JPRH 0703-221M - ☐	220	1	1.650	0.35
20	JPRH 0703-271M - ☐	270	1	2.310	0.32
21	JPRH 0703-331M - ☐	330	1	2.620	0.28
22	JPRH 0703-391M - ☐	390	1	2.940	0.26
23	JPRH 0703-471M - ☐	470	1	4.180	0.24
24	JPRH 0703-561M - ☐	560	1	4.670	0.22
25	JPRH 0703-681M - ☐	680	1	5.730	0.19
26	JPRH 0703-821M - ☐	820	1	6.540	0.18
27	JPRH 0703-102M - ☐	1000	1	9.440	0.16

Tolerance : M ± 20% , M tolerance is standard.

☐ : Revision of specification

PACKAGE

Type	JPRH 0703
Q'TY/Reel	1,000