



DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 1204	12.5 Max.	12.5 Max.	5.0 Max.	2.80	7.00	5.40

SERIES LIST

No.	Part No.	L (μ H)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRH 1204-6R8M - ☐	6.8	100	0.022	5.60
2	JPRH 1204-100M - ☐	10	100	0.028	4.50
3	JPRH 1204-150M - ☐	15	100	0.050	3.20
4	JPRH 1204-220M - ☐	22	100	0.066	2.90
5	JPRH 1204-330M - ☐	33	100	0.097	2.70
6	JPRH 1204-390M - ☐	39	100	0.132	2.10
7	JPRH 1204-470M - ☐	47	100	0.150	1.90
8	JPRH 1204-680M - ☐	68	100	0.220	1.50
9	JPRH 1204-101M - ☐	100	100	0.402	1.30
10	JPRH 1204-121M - ☐	120	100	0.380	1.10
11	JPRH 1204-151M - ☐	150	100	0.530	0.95
12	JPRH 1204-221M - ☐	220	100	0.700	0.80
13	JPRH 1204-331M - ☐	330	100	0.990	0.50

Tolerance : M $\pm$ 20% , M tolerance is standard.

☐ : Revision of specification

PACKAGE

Type	JPRH 1204
Q'TY/Reel	500