



LAND PATTERNS(mm)

DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 1207	12.0 ± 0.3	12.0 ± 0.3	8.0 Max.	2.90	7.00	5.40

SERIES LIST

No.	Part No.	L (μH)	Test Frequency (Hz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRH 1207-1R0M - ☐	1.0	100K	0.0065	14.00
2	JPRH 1207-2R4M - ☐	2.4	100K	0.0105	10.30
3	JPRH 1207-3R5M - ☐	3.5	100K	0.0124	9.30
4	JPRH 1207-4R6M - ☐	4.6	100K	0.0138	9.10
5	JPRH 1207-5R8M - ☐	5.8	100K	0.0170	8.60
6	JPRH 1207-7R4M - ☐	7.4	100K	0.0177	7.40
7	JPRH 1207-100M - ☐	10	1K	0.0195	6.70
8	JPRH 1207-120M - ☐	12	1K	0.0213	6.45
9	JPRH 1207-150M - ☐	15	1K	0.0264	5.65
10	JPRH 1207-180M - ☐	18	1K	0.0280	5.10
11	JPRH 1207-220M - ☐	22	1K	0.0364	4.70
12	JPRH 1207-270M - ☐	27	1K	0.0416	4.20
13	JPRH 1207-330M - ☐	33	1K	0.0533	3.90
14	JPRH 1207-390M - ☐	39	1K	0.0605	3.50
15	JPRH 1207-470M - ☐	47	1K	0.0780	3.25
16	JPRH 1207-560M - ☐	56	1K	0.0900	2.90
17	JPRH 1207-680M - ☐	68	1K	0.1200	2.60
18	JPRH 1207-820M - ☐	82	1K	0.1190	2.40
19	JPRH 1207-101M - ☐	100	1K	0.1510	2.10
20	JPRH 1207-121M - ☐	120	1K	0.1690	1.90
21	JPRH 1207-151M - ☐	150	1K	0.2270	1.80
22	JPRH 1207-181M - ☐	180	1K	0.2990	1.55
23	JPRH 1207-221M - ☐	220	1K	0.3380	1.45
24	JPRH 1207-271M - ☐	270	1K	0.4190	1.30
25	JPRH 1207-331M - ☐	330	1K	0.4710	1.20
26	JPRH 1207-391M - ☐	390	1K	0.5720	1.10
27	JPRH 1207-471M - ☐	470	1K	0.7410	1.00
28	JPRH 1207-561M - ☐	560	1K	0.8520	0.95
29	JPRH 1207-681M - ☐	680	1K	1.1300	0.85
30	JPRH 1207-821M - ☐	820	1K	1.2400	0.75
31	JPRH 1207-102M - ☐	1000	1K	1.5000	0.70
32	JPRH 1207-152M - ☐	1200	1K	2.3740	0.60
33	JPRH 1207-202M - ☐	2000	1K	3.0200	0.48

Tolerance : M ± 20% , M tolerance is standard.

☐ : Revision of specification

PACKAGE

Type	JPRH 1207
Q'TY/Reel	500