



LAND PATTERNS(mm)

DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 1209	12.5 Max.	12.5 Max.	10.0 Max.	2.90	7.00	5.40

SERIES LIST

No.	Part No.	L (μ H)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRH 1209-1R0M - □	1.0	100	0.0038	16.00
2	JPRH 1209-2R2M - □	2.2	100	0.0074	12.00
3	JPRH 1209-4R7M - □	4.7	100	0.0128	11.00
4	JPRH 1209-6R8M - □	6.8	100	0.0163	8.80
5	JPRH 1209-8R2M - □	8.2	100	0.0170	7.30
6	JPRH 1209-100M - □	10	1	0.0210	7.10
7	JPRH 1209-150M - □	15	1	0.0217	7.00
8	JPRH 1209-220M - □	22	1	0.0395	6.00
9	JPRH 1209-270M - □	27	1	0.0416	6.00
10	JPRH 1209-330M - □	33	1	0.0580	4.30
11	JPRH 1209-390M - □	39	1	0.0660	4.20
12	JPRH 1209-470M - □	47	1	0.0613	4.00
13	JPRH 1209-560M - □	56	1	0.0734	4.20
14	JPRH 1209-680M - □	68	1	0.0885	3.40
15	JPRH 1209-820M - □	82	1	0.1120	3.10
16	JPRH 1209-101M - □	100	1	0.1599	2.60
17	JPRH 1209-121M - □	120	1	0.1638	2.60
18	JPRH 1209-151M - □	150	1	0.1900	2.30
19	JPRH 1209-181M - □	180	1	0.2095	2.10
20	JPRH 1209-221M - □	220	1	0.2400	2.20
21	JPRH 1209-271M - □	270	1	0.3560	1.80
22	JPRH 1209-331M - □	330	1	0.3860	1.50
23	JPRH 1209-391M - □	390	1	0.4760	1.80
24	JPRH 1209-471M - □	470	1	0.5380	1.50
25	JPRH 1209-561M - □	560	1	0.7755	1.30
26	JPRH 1209-681M - □	680	1	0.8690	1.40
27	JPRH 1209-102M - □	1000	1	1.2263	1.00
28	JPRH 1209-122M - □	1200	1	1.7200	0.75
29	JPRH 1209-202M - □	2000	1	2.5000	0.60
30	JPRH 1209-222M - □	2200	1	2.7000	0.55
31	JPRH 1209-272M - □	2700	1	4.0200	0.50
32	JPRH 1209-302M - □	3000	1	3.2000	0.50
33	JPRH 1209-402M - □	4000	1	5.2000	0.45
34	JPRH 1209-682M - □	6800	1	11.600	0.30

Tolerance : M $\pm$ 20% , M tolerance is standard.

☐ : Revision of specification

■ PACKAGE

Type	JPRH 1209
Q'TY/Reel	250