



DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRD 1004	10.0 ± 0.3	10.5 Max.	3.8 ± 0.2	1.70	7.30	3.60

SERIES LIST

No.	Part No.	L (μ H)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRD 1004-1R5N - □	1.5	100	0.0114	9.00
2	JPRD 1004-2R2M - □	2.2	100	0.0123	7.80
3	JPRD 1004-3R8M - □	3.8	100	0.0130	6.00
4	JPRD 1004-5R2M - □	5.2	100	0.0220	5.50
5	JPRD 1004-5R6M - □	5.6	100	0.0231	5.30
6	JPRD 1004-6R8M - □	6.8	100	0.0270	4.80
7	JPRD 1004-7R0M - □	7.0	100	0.0350	4.80
8	JPRD 1004-8R2M - □	8.2	100	0.0334	4.40
9	JPRD 1004-100M - □	10.0	100	0.0350	4.40
10	JPRD 1004-150M - □	15.0	100	0.0500	3.60
11	JPRD 1004-220M - □	22.0	100	0.0730	2.90
12	JPRD 1004-270M - □	27.0	100	0.0930	2.30
13	JPRD 1004-330M - □	33.0	100	0.1440	2.30
14	JPRD 1004-470M - □	47.0	100	0.1356	2.10
15	JPRD 1004-560M - □	56.0	100	0.1910	1.50
16	JPRD 1004-680M - □	68.0	100	0.2130	1.50
17	JPRD 1004-101M - □	100	100	0.3040	1.35
18	JPRD 1004-151M - □	150	100	0.5060	1.15
19	JPRD 1004-221M - □	220	100	0.7560	0.92
20	JPRD 1004-331M - □	330	100	1.0900	0.70
21	JPRD 1004-471M - □	470	100	1.6100	0.50
22	JPRD 1004-561M - □	560	100	2.2000	0.40

Tolerance : M = ± 20% , N = ± 30%

□ : Revision of specification

PACKAGE

Type	JPRD 1004
Q'TY/Reel	500