



LAND PATTERNS(mm)

DIMENSIONS (mm)

Part No.	A	B	C
JSB 0603	6.0 ± 0.2	6.0 ± 0.2	3.2 Max.

SERIES LIST

No.	Part No.	L (μ H)	Test Frequency (KHz)	RDC (Ω) (max)	IDC (A) (max)
1	JSB 0603-1R0M - ☐	1.00	1	0.026	4.500
2	JSB 0603-2R0M - ☐	2.00	100	0.028	3.500
3	JSB 0603-3R3M - ☐	3.30	100	0.034	3.000
4	JSB 0603-4R7M - ☐	4.70	100	0.053	2.500
5	JSB 0603-6R8M - ☐	6.80	1	0.053	2.200
6	JSB 0603-100M - ☐	10.0	1	0.077	1.800
7	JSB 0603-101M - ☐	100	1	0.990	0.640
8	JSB 0603-221M - ☐	220	1	3.550	0.200
9	JSB 0603-471M - ☐	470	1	8.680	0.190
10	JSB 0603-602M - ☐	6000	1	73.00	0.045
11	JSB 0603-153M - ☐	15000	1	112.0	0.035
12	JSB 0603-223M - ☐	22000	1	219.6	0.030

DCR & IDC listed are all Max. value.

Tolerance : M $\pm$ 20% , M tolerance is standard.

☐ : Revision of specification

PACKAGE

Type	JSB 0603
Q'TY/Reel	1,000