



LAND PATTERNS(mm)

DIMENSIONS (mm)

Part No.	A	B	C
JSB 0705	7.6 Max.	7.6 Max.	5.1 Max.

SERIES LIST

No.	Part No.	L (μ H)	RDC (Ω) (max)	IDC (A) (max)
1	JSB 0705-1R0M - ☐	1.0	0.020	2.80
2	JSB 0705-1R5M - ☐	1.5	0.024	2.59
3	JSB 0705-2R2M - ☐	2.2	0.028	2.38
4	JSB 0705-3R3M - ☐	3.3	0.034	2.14
5	JSB 0705-4R7M - ☐	4.7	0.039	1.96
6	JSB 0705-6R8M - ☐	6.8	0.050	1.79
7	JSB 0705-100M - ☐	10	0.055	1.63
8	JSB 0705-120M - ☐	12	0.073	1.42
9	JSB 0705-150M - ☐	15	0.090	1.33
10	JSB 0705-180M - ☐	18	0.102	1.15
11	JSB 0705-220M - ☐	22	0.115	1.09
12	JSB 0705-270M - ☐	27	0.159	0.91
13	JSB 0705-330M - ☐	33	0.182	0.84
14	JSB 0705-390M - ☐	39	0.199	0.80
15	JSB 0705-470M - ☐	47	0.221	0.75
16	JSB 0705-560M - ☐	56	0.306	0.64
17	JSB 0705-680M - ☐	68	0.345	0.60
18	JSB 0705-820M - ☐	82	0.390	0.57
19	JSB 0705-101M - ☐	100	0.432	0.50
20	JSB 0705-121M - ☐	120	0.440	0.50
21	JSB 0705-151M - ☐	150	0.730	0.40
22	JSB 0705-181M - ☐	180	0.780	0.39
23	JSB 0705-221M - ☐	220	0.940	0.33
24	JSB 0705-271M - ☐	270	1.250	0.31
25	JSB 0705-331M - ☐	330	1.400	0.27
26	JSB 0705-471M - ☐	470	1.700	0.25
27	JSB 0705-561M - ☐	560	2.390	0.22

Test frequency is 100KHz.

DCR & IDC listed are all Max. value.

Tolerance : M $\pm$ 20% , M tolerance is standard.

☐ : Revision of specification

PACKAGE

Type	JSB 0705
Q'TY/Reel	1,000