


SPECIFICATION FOR APPROVAL

COMMODITY	COMMON MODE FILTER CHOKE	SPEC NO.	SP-0220802001
ITEM	JSCM 1513V-551 Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
		A	15.0 ±0.5
		B	13.0 ±0.4
		C	6.0 MAX.
		D	9.3 TYP.
		E	2.7 ±0.5
		F	3.6 ±0.5
		G	2.8 ±0.5

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
IMPEDANCE	450 (min.) Ω 550 (typ.)	☒ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter
TEST FREQUENCY	100 MHz	☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
RDC (1 line)	4 (max.) m Ω	☒ CHROMA 3302 Automatic Components Analyzer.
Rated Current	10 (max.) A	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
Rated Volt.	125 (max) Vdc	☒ ZENTECH 1320 BIAS CURRENT.
Insulation Resistance	10 (min) M Ω	☒ BK PRECISION 2840 DC Resistance Meter ☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter
		☒ WAYNE KERR HI-POT TESTER 7600

REMARK :


- Operating temperature range : - 40℃ to + 125℃ (Including self temp. rise)
- Storage temperature range : -40~+125℃ (on board)
- Marking : Laser Marking
- Compatible with AEC-Q200

PURCHASER CONFIRMED :	APPROVED	CHECKED	DRAWN
			

TEST REPORT

SPEC NO : SP-0220802001

Typical Performance Curves



Check by :

姜秀琴

Test by :

陳秀月