


SPECIFICATION FOR APPROVAL

COMMODITY	Molding SMD Power Coils	SPEC NO.	SP-0230717007
ITEM	JRPI 0502MH-1R0M Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	5.70	± 0.30
	A1	5.20	± 0.30
	B	5.30	± 0.20
	C	2.80	± 0.20
	D	1.20	± 0.30
	E	3.00	± 0.30

(2) ELECTRICAL CHARACTERISTIC		TEST INSTRUMENTS.
INDUCTANCE	1.0 ± 20% μ H	☐ AGILENT 4294A Precision Impedance Analyzer ☐ Agilent 4287A RF LCR Meter ☐ AGILENT 4285A Precision L.C.R. ☐ HP-4286A RF L.C.R. Meter.
TEST FREQUENCY	100 KHz	☒ CHROMA 3302 Automatic Components Analyzer.
TEST VOLT	1 V	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
RDC	5.6 (typ.) 6.7 (max) $m\Omega$	☒ ZENTECH 1320 BIAS CURRENT.
Isat	16.0 (typ.) 13.5 (max) A	☒ BK PRECISION 2840 DC Resistance Meter
Irms	15.0 (typ.) 13.0 (max) A	☐ ZENTECH 502AC Resistance Merter ☐ ADEX AX-1155B DC Low Ohm Meter
		☐ WAYNE KERR HI-POT TESTER 7600

REMARK :

1. All test data referenced to 25°C ambient.
2. Saturation Current (Isat) will cause L0 to drop approximately 30%
3. Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C


PURCHASER CONFIRMED :

APPROVED	CHECKED	DRAWN
		

TEST REPORT

SPEC NO : SP-0230717007

Typical Performance Curves



Test Instrument :

Chroma 3302 Automatic Components Analyzer
ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28 $^{\circ}C$
Humidity : 60 to 70 % RH

Check by :



Test by :



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw